

Flush-mounting cabinets Practibox³

from 18 to 72 modules



4 017 09 4 017 08 4 017 07 4 017 06



4 017 19 4 017 18 4 017 17 4 017 16



0 019 66

Technical characteristics p. 209

Class II
IP 40 - IK 07 with door
Self-extinguishing: resistance to incandescent wire 850 °C
Conform to IEC 60670-24 and IEC 62208 : allows to achieve assemblies conform to IEC 61439-3

Pack	Cat.Nos		Flush-mounting distribution cabinets				
			Capacity 18 modules per row Box for masonry or dry partitions (with dry partitions kit Cat.No 4 017 24) Supplied with: - removable chassis with rails fitted - reversible door (door + faceplate for 1-row cabinets) - removable faceplates for each row (for 2, 3 and 4-row cabinets) - IP 2X screw terminal blocks - blanking plates (5 modules, separable per module or 1/2 module, for 2, 3 and 4-row cabinets) Spacing between rails 150 mm Door opening : 180° Can be equipped with lock and key n° 850 Cat.No 0 019 66				
			With transparent door				
	With earth terminal blocks	With earth and neutral terminal blocks	Number of rows	Number of modules	Height (mm)	Width (mm)	Flush-mounting box depth (mm)
1	4 017 06	4 017 56	1	18	234	422	85
1	4 017 07	4 017 57	2	36	442	422	85
1	4 017 08	4 017 58	3	54	592	422	91
1	4 017 09	4 017 59	4	72	742	422	91
			With white door RAL 9003				
1	4 017 16	4 017 66	1	18	234	422	85
1	4 017 17	4 017 67	2	36	442	422	85
1	4 017 18	4 017 68	3	54	592	422	91
1	4 017 19	4 017 69	4	72	742	422	91

Pack	Cat.Nos	Accessories
1	4 017 23	Horizontal or vertical joining kit For joining 2 cabinets when installed in masonry
1	4 017 24	Flush-mounting kit for dry partitions For installation of Practibox ³ cabinets in dry partitions
1	4 017 22	Horizontal partition For 2, 3 or 4-rows cabinets
1	4 017 25	Plain faceplate For 2, 3 or 4-rows cabinets Allow fitting of non-modular equipments such as control and signalling units
1	4 017 26	Perforated plates To be used instead of the one rail when integrating non-modular products For 2, 3 or 4-rows cabinets Height 150 mm
1	4 017 27	12x2 flat bar for IP 2X terminal blocks For 2, 3 or 4-rows cabinets Allow fitting of additional IP 2X terminal blocks
1	0 019 66	Key lock To be fitted on white or transparent doors Supplied with key n° 850
		Blanking plates White RAL 9003 Separable per module or 1/2 module
20	0 016 60	5 modules
10	0 016 62	13 modules
10	0 016 64	18 modules

