




Insulated twin cable end-sleeves 0.25 - 16 mm²

For fine and superfine stranded conductors
For multi purpose use of clamps
Colour coded based on DIN 46228 part 4 (0.5 - 16 mm²)

Characteristics

- Insulated, free of halide
- Heat resistant to 105° C
- Easy-Entry insulation for simple cable insertion

Material

- Copper to EN 13600
- Synthetic material: polypropylene

Surface

- tin plated



Article

Nominal cross section mm ²	Part No.	Colour	d1	d3	l1	l2	s1	s2	Packing unit/pcs
2 x 0,25	8678	■	1,15	1,8/3,4	15,0	8	0,15	0,25	1000
2 x 0,34	8688	■	1,15	1,8/3,4	15,0	8	0,15	0,25	1000
2 x 0,5	8698	□	1,50	2,5/4,7	15,0	8	0,15	0,25	1000
2 x 0,75	87010	■	1,80	2,8/5,0	17,0	10	0,15	0,25	1000
2 x 0,75	8708	■	1,80	2,8/5,0	15,0	8	0,15	0,25	1000
2 x 1	8718	■	2,05	3,4/5,4	15,0	8	0,15	0,30	1000
2 x 1	87110	■	2,05	3,4/5,4	17,0	10	0,15	0,30	1000
2 x 1,5	8728	■	2,30	3,6/6,6	16,0	8	0,15	0,30	1000
2 x 1,5	87212	■	2,30	3,6/6,6	20,0	12	0,15	0,30	1000
2 x 10	87614	■	6,50	7,2/13,0	26,0	14	0,20	0,40	100
2 x 16	87714	■	8,30	9,6/18,4	30,0	14	0,20	0,40	100
2 x 2,5	87310	■	2,90	4,2/7,8	18,5	10	0,20	0,30	100
2 x 2,5	87313	■	2,90	4,2/7,8	21,5	13	0,20	0,30	100
2 x 4	87412	■	3,80	4,9/8,8	23,0	12	0,20	0,30	100
2 x 6	87514	■	4,90	6,9/10,0	26,0	14	0,20	0,40	100

