

MCBs DX³ [6000] - 10 kA

thermal magnetic circuit breakers from 1 A to 63 A - B and C curves




4 074 35




4 078 02



4 075 65



4 079 34



Technical characteristics [see e-catalogue](#)

Conform to IEC 60898-1

Compatible with both, prong-type and fork type supply busbars

Breaking capacity

[6000] - IEC 60898-1 - 400 V~

10 kA - IEC 60947-2 - 400 V~

Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls (p. 64) and add-on modules (p. 62)

Pack	Cat.Nos		Single pole 230/400 V~		Pack	Cat.Nos		3-pole 400 V~	
	B curve	C curve	Nominal rating In (A)	Number of modules		B curve	C curve	Nominal rating In (A)	Number of modules
1	4 074 25	4 076 62	1	1	1	4 075 54	4 078 51	1	3
1	4 074 26	4 076 63	2	1	1	4 075 55	4 078 52	2	3
1	4 074 27	4 076 64	3	1	1	4 075 56	4 078 53	3	3
1	4 074 28	4 076 65	4	1	1	4 075 57	4 078 54	4	3
10	4 074 29	4 076 66	6	1	1	4 075 58	4 078 55	6	3
10	4 074 30	4 076 68	10	1	1	4 075 59	4 078 57	10	3
1	4 074 31	4 076 69	13	1	1	4 075 60	4 078 58	13	3
10	4 074 32	4 076 70	16	1	1	4 075 61	4 078 59	16	3
10	4 074 33	4 076 71	20	1	1	4 075 62	4 078 60	20	3
10	4 074 34	4 076 72	25	1	1	4 075 63	4 078 61	25	3
10	4 074 35	4 076 73	32	1	1	4 075 64	4 078 62	32	3
1	4 074 36	4 076 74	40	1	1	4 075 65	4 078 63	40	3
1	4 074 37	4 076 75	50	1	1	4 075 66	4 078 64	50	3
1	4 074 38	4 076 76	63	1	1	4 075 67	4 078 65	63	3

	B curve	C curve	Nominal rating In (A)	Number of modules		B curve	C curve	Nominal rating In (A)	Number of modules
1	4 074 68	4 077 34	1	1	1	4 076 17	4 079 20	1	4
1	4 074 69	4 077 35	2	1	1	4 076 18	4 079 21	2	4
1	4 074 70	4 077 36	3	1	1	4 076 19	4 079 22	3	4
1	4 074 71	4 077 37	4	1	1	4 076 20	4 079 23	4	4
1	4 074 72	4 077 38	6	1	1	4 076 21	4 079 24	6	4
1	4 074 73	4 077 40	10	1	1	4 076 22	4 079 26	10	4
1	4 074 74	4 077 41	13	1	1	4 076 23	4 079 27	13	4
10	4 074 75	4 077 42	16	1	1	4 076 24	4 079 28	16	4
1	4 074 76	4 077 43	20	1	1	4 076 25	4 079 29	20	4
1	4 074 77	4 077 44	25	1	1	4 076 26	4 079 30	25	4
1	4 074 78	4 077 45	32	1	1	4 076 27	4 079 31	32	4
1	4 074 79	4 077 46	40	1	1	4 076 28	4 079 32	40	4
					1	4 076 29	4 079 33	50	4
					1	4 076 30	4 079 34	63	4

	B curve	C curve	Nominal rating In (A)	Number of modules
1	4 075 02	4 077 92	1	2
1	4 075 03	4 077 93	2	2
1	4 075 04	4 077 94	3	2
1	4 075 05	4 077 95	4	2
115	4 075 06	4 077 96	6	2
115	4 075 07	4 077 98	10	2
1	4 075 08	4 077 99	13	2
115	4 075 09	4 078 00	16	2
115	4 075 10	4 078 01	20	2
115	4 075 11	4 078 02	25	2
115	4 075 12	4 078 03	32	2
1	4 075 13	4 078 04	40	2
1	4 075 14	4 078 05	50	2
1	4 075 15	4 078 06	63	2