



# Isolating switches RX<sup>3</sup>

from 40 A to 80 A



# RCCBs RX<sup>3</sup>

residual current circuit breakers from 25 A to 63 A - AC and A types



Dimensions **see e-catalogue**

Conform to IEC 60947-3  
 Grey handle  
 AC 22 A  
 Compatible with prong-type and fork type supply busbars  
 Do not accept auxiliaries

Dimensions **see e-catalogue**

Conform to IEC 61008-1  
 • AC type : detect AC component faults  
 • A type : detect AC and DC component faults  
 Compatible with prong-type and fork type supply busbars  
 Do not accept auxiliaries

Pack	Cat.Nos	Isolating switches	
		<b>2P - 400 V~</b>	
		Nominal rating In (A)	Number of modules
6	4 193 24	40	2
6	4 193 25	63	2
6	4 193 26	80	2
		<b>3P - 400 V~</b>	
1	4 193 27	40	3
1	4 193 28	63	3
1	4 193 29	80	3
		<b>4P - 400 V~</b>	
1	4 193 30	40	4
1	4 193 31	63	4
1	4 193 32	80	4

Pack	Cat.Nos	2-pole - 230 V~		
		<b>AC type</b>		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 24	30	25	2
1	4 020 25	30	40	2
1	4 020 26	30	63	2
1	4 020 27	30	80	2
1	4 020 28	100	25	2
1	4 020 29	100	40	2
1	4 020 30	100	63	2
1	4 020 32	300	25	2
1	4 020 33	300	40	2
1	4 020 34	300	63	2
		<b>A type</b>		
1	4 020 36	30	25	2
1	4 020 37	30	40	2
1	4 020 38	30	63	2
		<b>4-pole - 400 V~ neutral on right-hand side</b>		
		<b>AC type</b>		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 62	30	25	4
1	4 020 63	30	40	4
1	4 020 64	30	63	4
1	4 020 66	100	25	4
1	4 020 67	100	40	4
1	4 020 68	100	63	4
1	4 020 70	300	25	4
1	4 020 71	300	40	4
1	4 020 72	300	63	4
		<b>A type</b>		
1	4 020 74	30	25	4
1	4 020 75	30	40	4
1	4 020 76	30	63	4

For detailed dimensions, **see e-catalogue**

