

## Plexo™ 66 complete flush-mounting

IP 66 - IK 08



6 845 53



6 845 56



6 845 70

White RAL 9010  
 Polypropylene/ABS housing  
 Temperature rating: - 20 to + 40 °C (+ 50 °C for short periods)  
 Supplied without back boxes, can mount directly on to standard metal flush boxes  
 Stainless steel captive terminal screws supplied in backed-off position  
 Supplied with flush-mounting gasket  
 Supplied without lamps

Pack	Cat.Nos	20 A - 250 V~ switches
1	6 845 53	Conform to BS EN 60669-1 Flush-mounting gasket is not required when fitting these mechanisms on to back boxes Cat.Nos 6 845 89/90/91 1 gang 2 way switch - SP
1	6 845 54	2 gang 2 way SP
1	6 845 56	1 gang 1 way DP + indicator
1	6 845 60	<b>6 A - 250 V~ push-button</b> 1 gang 2 way SP retractive switch
1	6 845 70	<b>13 A - 250 V~ socket outlet</b> Conforms to BS 1363 : Part 2 1 gang unswitched
1	6 845 85	<b>Arteor/Mosaic adaptor</b> 2 modules with opaque lid

## Plexo™ 66 complete surface-mounting

IP 66 - IK 08



6 846 19



0 904 67

Grey RAL 7016/TO 29  
 Supplied with ISO 20 membrane glands and caps for rear cabling  
 For top or down cabling, plastic cable glands (p. 315) have to be used  
 Stainless steel captive terminal screws supplied in backed-off position

Pack	Cat.Nos	20 A - 250 V~ switches
1	6 846 03	Conform to BS EN 60669-1 Fitted with rear gasket with groove to deposit silicone 1 gang Two-way switch - SP
1	6 846 02	1 gang One way switch - DP
1	6 846 04	2 gang Two-way switch - SP
1	6 846 11	<b>6 A - 250 V~ push-buttons</b> 1 gang Two-way switch - SP with "Bell"
1	6 846 45	<b>13 A - 250 V~ fused spur unit</b> Conform to BS 1363: Part 4 Fitted with rear gasket with groove to deposit silicone 1 gang - DP switched
1	6 846 22	<b>13 A - 250 V~ socket outlets</b> Conform to BS 1363: Part 2 Fitted with rear gasket with groove to deposit silicone 1 gang Switched socket with opaque lid
1	6 846 20	1 gang Unswitched socket with opaque lid
1	6 846 19	1 gang unswitched Accepts moulded plugs with side outlet
1	6 846 28	2 gang unswitched
1	0 904 67	<b>RJ 45 socket</b> Cat.6 - FTP
1	6 846 36	<b>Arteor/Mosaic adaptors</b> 2 module adaptor - semi-transparent lid
1	6 846 38	3 module adaptor - semi-transparent lid